

FARMALL B

25 | 35 | 50 | 60 HP TRACTORS



CASE IH

FARMALL 25B

Performance & agility in a powerful, small-chassis compact tractor



With its proven three cylinder, high torque diesel engine and easy to operate two-range hydrostatic transmission, this purpose built compact tractor is the perfect for pulling trailers and light implements, mowing and front loader work.

STANDARD 2000 RPM Mid PTO for optional height adjustable 60" mid-mount mower that produces a smooth and beautiful cut.

HYDROSTATIC TRANSMISSION Maximises ease of use with effortless, clutch-less and instant speed and directional changes with a simple push of the pedals.

MODELS	TYPE	SIZE	HP (KW)	TORQUE	FUEL TANK	REAR LIFT CAPACITY	DRY WEIGHT	FRONT END LOADER	BUCKET TYPE	MAX LIFT HEIGHT	LIFT CAPACITY
Farmall B25	3 cyl diesel	1.32 l	27 (20)	79 Nm	25 litres	650kg	730kg	PLc05	Standard or 4-in-1	1.85m	200kg

FARMALL 35B

The mighty 38 hp helper for the serious lifestyle farmer



With its fuel efficient 4-cylinder engine and 1,385kg dry weight, the Farmall 35B takes lifestyle farming to a whole new level. With a host of standard features normally found on larger tractors, it's no wonder the Farmall 35B is the most popular model in the Case IH lifestyle range. Hydro and Synchro options.

MODELS	TRANS	TYPE	SIZE	HP (KW)	TORQUE	FUEL TANK	REAR LIFT CAPACITY	WEIGHT	FRONT END LOADER	BUCKET TYPE	MAX LIFT HEIGHT	LIFT CAPACITY
Farmall 35B	Hydrostatic/ Mechanical	4 cyl diesel	1.76 l	38 (28)	103 Nm	33 litres	820kg	Mech 1385kg / Hydro 1403kg	PLc10	Standard or 4-in-1	2.45m	375kg

FARMALL 50B

The professional's choice

2.5L four cylinder diesel power matched with either a three range hydro or 16x16 synchro transmission means you're always prepared for the toughest challenge. Choose from ag, turf, or industrial tyre options.

POWERFUL 3-POINT HITCH The powerful 3-point hitch lift capacity of 1,830kg allows usage of a wide variety of implements

DASH PANEL All the important functional data is yours at a glance to keep you in better control of your tractor.



MODELS	TRANS	TYPE	SIZE	HP (KW)	TORQUE	FUEL TANK	REAR LIFT CAPACITY	DRY WEIGHT	FRONT END LOADER	BUCKET TYPE	MAX LIFT HEIGHT	LIFT CAPACITY
Farmall 50B	Hydrostatic/ Mechanical	4 cyl diesel	2.5 l	47 (35)	140 Nm	36 litres	1252kg	Mech 1650kg / Hydro 1680kg	PLc15	Standard or 4-in-1	2.7m	420kg

FARMALL 60B

The perfect all-rounder. Available in Cab or ROPS.

The Farmall 60B is the heavyweight of the Case IH lifestyle range. Its turbocharged engine delivers effortless power – and an array of impressive features such as two sets of hydraulic remotes and three-speed PTO are fitted as standard.



MODELS	TYPE	SIZE	HP (KW)	TORQUE	FUEL TANK	REAR LIFT CAPACITY	DRY WEIGHT	FRONT END LOADER	BUCKET TYPE	MAX LIFT HEIGHT	LIFT CAPACITY
Farmall 60B	4 cyl diesel	2.5 l	57 (43)	170 Nm	80 litres	1252kg	1850kg	PLc25	Standard or 4-in-1	2.9m	810kg ROPS/ 725kg Cab

FARMALL B SERIES TRACTOR SPECIFICATIONS	FARMALL 25B	FARMALL 35B	FARMALL 50B	FARMALL 60B
ENGINE				
Gross (HP/kW)	27 (20)	38 (28)	47 (35)	57 (43)
Max Torque (Nm)	79	103	140	170
Aspiration		Natural		Turbo
Cylinders	3	4	4	4
Displacement	1.318	1.758	2.505	2.505
Rated speed (RPM)		2700		2600
Fuel tank capacity (Ltr)	33	33	36	80
PTO				
PTO Speed		540		540/750/1000
PTO Type		Electro-Hydraulic Independent		
TRANSMISSION				
Mechanical				
Ranges	N/A	12 x 12	16 x 16	16 x 16
Speed Range (kph)	N/A	1.2 - 24	1.2 - 27	1.2 - 32
Hydrostatic				
Ranges	2	3	3	N/A
Speed Range (kph)	0 - 15.7	0 - 25	0 - 25	N/A
ELECTRICAL SYSTEM				
System Voltage (v)		12		
Alternator rating (A)		50amp		
Battery (CCA)	60AH	80AH		100AH
HYDRAULIC SYSTEM				
Type		Gear Pump		
Capacity - excludes steering and trans (l/min)	10	30	29	36
Remotes (std)	1	1 rear + joystick and 4 front outlets		
3 point Linkage Category		Cat. 1		Cat. 2
3 Point Linkage Capacity @ Ball Ends (kg)	650	820	1252	1850
Steering		Hydrostatic		
DIMENSIONS				
*Approximate Shipping Weight - (kg)	730	1403 - Hydro 1385 - Mech.	1680 - Hydro 1650 - Mech.	ROPS - 2165 Cab - 2370
*Ground Clearance - Under Drawbar (mm)	290	300	372	407
Wheelbase (mm)	1500	1674	1758	2047
*Overall Length (mm)	2660	2987	3192	3556
*Overall Width (mm)	1226	1333	1672	1700
*Overall Height (mm)	2370	2352	2447	2650 - ROPS 2465 - Cab
Turning Radius without Brakes (m)	2.62	3.05	3.08	3.3
Compatible loader specifications				
Loader model (prime lift compact)	PLCO5	PLCO10	PLCO15	PLCO25
*Lift Height (pivot pin)	1850mm	1850mm	1850mm	2900mm
Rated Operating Load - STD Bucket/Loader/Tractor	200kg	375kg	420kg	810kg ROPS/725kg Cab
Loader Lift Capacity kg - Max (Loader Only)	395kg	693kg	734kg	1131kg
Bucket Width mm (inches)	1340 (52)	1500 (59)	to 1700 (67)	to 1860 (73)
Counterweight Recommendation	230kg	245kg	350kg	810kg ROPS/725kg Cab

*Indicative only – Will vary depending on specification & wheel equipment

The data indicated in this folder are approximate.
The models described here can be modified without the manufacturer's notice. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please get in touch with our Dealer Network for any further information. Published by CNH Industrial. Printed for New Zealand - 11/22 - 10002/NZ

