

GOLD F



- Front loader with manual implement levelling
- Fitting brackets supporting loader from tractor front end to rear axle shafts
 - Hydraulic system conforming to tractor specifications

- Standard equipment**
- Two double acting cylinders for lifting
 - Two double acting cylinders for the operation of the implement
 - Quick-release of loader from tractor VELOTAK
 - Implement quick release EURO
 - Hydraulic quick-fit couplings
 - Adjustable support legs
 - Bucket level gauge
 - Anti-bounce GENIUS SYSTEM



GOLD F

Lifting force at 180 bar		F20	F30
with bucket on ground, at 300 mm from pivoting point	Q1 Kg	1500	1700
with bucket at max. height, at 300 mm from pivoting point	Q2 Kg	1400	1600
with fork on ground, at 600 mm from pivoting point	Q3 Kg	1500	1700
with fork at max. height, at 600 mm from pivoting point	Q4 Kg	1400	1600
tear out force at bucket tooth	Q5 Kg	2000	2000
Max. lifting height			
at pivoting point	A mm	3800	3870
with tilted bucket	B mm	2940	3010
Angles			
tilting bucket on ground	C °	45	45
bucket unloading	D °	55	55
Digging depth		E mm	150
Working duration L / 1' = 40			
Lifting at max. height	"	7	9
Bucket tilting	"	5	5
Weights			
Without implement and fitting brackets	Kg	440	473
HP		60-100	70-120



GOLD M


- Front loader with mechanical implement self-levelling system
- Fitting brackets supporting loader from tractor front end to rear axle shafts
 - Hydraulic system conforming to tractor specifications

- Standard equipment**
- Two double acting cylinders for lifting
 - Two double acting cylinders for the operation of the implement
 - Quick-release of loader from tractor VELOTAK
 - Implement quick release EURO
 - Hydraulic quick-fit couplings
 - Adjustable support legs
 - Bucket level gauge
 - Anti-bounce GENIUS SYSTEM



GOLD M

Lifting force at 180 bar		M20	M30
with bucket on ground, at 300 mm from pivoting point	Q1 Kg	1800	2000
with bucket at max. height, at 300 mm from pivoting point	Q2 Kg	1700	1900
with fork on ground, at 600 mm from pivoting point	Q3 Kg	1800	2000
with fork at max. height, at 600 mm from pivoting point	Q4 Kg	1700	1900
tear out force at bucket tooth	Q5 Kg	2000	2000
Max. lifting height			
at pivoting point	A mm	3800	3870
with tilted bucket	B mm	2940	3010
Angles			
tilting bucket on ground	C °	45	45
bucket unloading	D °	90	90
Digging depth		E mm	150
Working duration L / 1' = 40			
Lifting at max. height	"	7	7
Bucket tilting	"	5	5
Weights			
Without implement and fitting brackets	Kg	500	533
HP		60-100	70-120



GOLD H



- Front loader with hydraulic implement self-levelling system
- Fitting brackets supporting loader from tractor front end to rear axle shafts
 - Hydraulic system conforming to tractor specifications

- Standard equipment**
- Two double acting cylinders for lifting
 - Two double acting cylinders for the operation of the implement designed with double rod for faster implement unloading
 - Quick-release of loader from tractor VELOTAK
 - Implement quick release EURO
 - Hydraulic quick-fit couplings
 - Adjustable support legs
 - Bucket level gauge
 - Anti-bounce GENIUS SYSTEM



GOLD H

Lifting force at 180 bar		H20	H30
with bucket on ground, at 300 mm from pivoting point	Q1 Kg	1800	2000
with bucket at max. height, at 300 mm from pivoting point	Q2 Kg	1700	1900
with fork on ground, at 600 mm from pivoting point	Q3 Kg	1800	2000
with fork at max. height, at 600 mm from pivoting point	Q4 Kg	1700	1900
tear out force at bucket tooth	Q5 Kg	2000	2000
Max. lifting height			
at pivoting point	A mm	3800	3870
with tilted bucket	B mm	2940	3010
Angles			
tilting bucket on ground	C °	45	45
bucket unloading	D °	55	55
Digging depth		E mm	150
Working duration L / 1' = 40			
Lifting at max. height	"	7	7
Bucket tilting	"	3	3
Weights			
Without implement and fitting brackets	Kg	500	533
HP		60-100	70-120



NOTE: technical data and pictures are only illustrative and not binding, as those may vary as well depending on the tractor model fitted